

Model no.	MPS-660-02-4F-161	MPS-660-03-4F-161	MPS-660-04-4F-161
Freq(MHz)	600-6000	600-6000	600-6000
Split Loss(dB)	3.0	4.8	6.0
Insertion Loss(dB)	≤0.2(600-2700MHz) ≤0.3(2700-6000MHz)	≤0.2(600-2700MHz) ≤0.4(2700-3800MHz) ≤0.45(3800-4900MHz) ≤0.9(4900-6000MHz)	≤0.3(600-2700MHz) ≤0.55(2700-3800MHz) ≤0.75(3800-4900MHz) ≤1.3(4.9-6GHz)
VSWR	≤1.3	≤1.35	≤1.35
PIM3 (dBc)	≤-161dBc@2*43dBm (698-2700)	≤-161dBc@2*43dBm (698-2700)	≤-161dBc@2*43dBm (698-2700)
Total Input Power(W)	300	300	300
Impedance	50 ohm	50 ohm	50 ohm
Connector	4.3/10-female	4.3/10-female	4.3/10-female
Color	black	black	black
Temp(deg)	-35~+75	-35~+75	-35~+75
Application	Indoor or Outdoor, IP67	Indoor or Outdoor, IP67	Indoor or Outdoor, IP67
Remark	Install Bracket Include	Install Bracket Include	Install Bracket Include